

# PRODUCT DATA



# STRATA

GEOSYSTEMS (INDIA) PVT. LTD.

(A Joint Venture with Strata Systems Inc. U.S.A.)

ISO 9001 : 2008 Certified

## StrataGrid UX<sup>®</sup>

StrataGrid is a geogrid reinforcement for soil. These high performance geogrids are constructed of high molecular weight and high tenacity knitted polyester yarns with a proprietary coating. StrataGrid is engineered to be mechanically and chemically durable, in both the harsh construction installation phase and in the aggressive soil environments.

	UNIT	SG150	SG200	SG350	SG500	SG550	SG600	SG700	SG800	SG900	SG1000
--	------	-------	-------	-------	-------	-------	-------	-------	-------	-------	--------

### Mechanical Properties (ASTM D 6637)

<b>Tensile Strength</b>	MD	kN/m	30.0	52.5	73.0	93.4	118.9	132.8	172.2	200.0	250.0	300.0
	CD	kN/m	20	20	30	30	30	30	30	30	30	30

<b>Creep Reduction Factor</b> (ASTM D 5262, ASTM D 6992)			1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46	1.46
---	--	--	------	------	------	------	------	------	------	------	------	------

<b>Creep Limited Strength</b>	kN/m		20.5	35.9	50.0	63.9	81.4	90.9	117.9	136.9	171.2	205.4
-------------------------------	------	--	------	------	------	------	------	------	-------	-------	-------	-------

### Partial Factor-Installation Damage

In clay, silt or sand			1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05	1.05
In sandy gravel			1.10	1.10	1.10	1.10	1.10	1.10	1.10	1.10	1.10	1.10
In gravel			1.20	1.20	1.20	1.20	1.20	1.20	1.20	1.20	1.20	1.20

### Partial Factor-Environmental Effects

(GRI-GG7, GRI-GG8)

Environment, $4 \leq \text{pH} \leq 8$			1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1	1.1
--	--	--	-----	-----	-----	-----	-----	-----	-----	-----	-----	-----

### Geometric Properties

<b>Grid Aperture Sizes</b>	MD	mm	24	17	20, 14	60	21, 8	60	50,11	61	60	50
	CD	mm	21	18	15	23	24	22	19	17	19	18

#### Notes:

Maximum roll width is 1.9m/3.8 m.

MD= machine direction/ CD= cross direction

Reported ultimate tensile strengths are average (typical) values obtained in accredited testing laboratories.

**Strata Systems, Inc.** has refined the science of soil reinforcement worldwide. **Strata Geosystems (India) Private Limited** is a joint venture company in India with Strata Systems, Inc. US. Strata India is manufacturing the whole range of Strata soil reinforcement products in India and is offering the highest level of technical expertise, customer service, and overall value. Fully staffed with experienced engineers, Strata India is carrying forward the same ideals and principles of quality and technical capabilities that Strata has employed in the U.S. Strata's success is a direct result of the power of StrataGrid<sup>®</sup> performance and its ability to solve complex civil engineering problems. StrataGrid<sup>®</sup> interacts with the soil particles to create a permanent composite soil-geosynthetic structure. These high performance geogrids are constructed of super high tenacity polyester yarn utilizing a complex knitting process to provide superior engineering properties.

UX.5.09/11

**Head Office:** 317, Tantia Jogani Industrial Premises, J. R. Boricha Marg, Lower Parel (E), Mumbai – 400 011, India.

**Phone:** +91 22 4063 5100 | **Fax:** +91 22 4063 5199

**Hyderabad Office:** 416, Maheshwari Chambers, 6-3-650, Somajiguda, Hyderabad – 500 082, India.

**Email:** [info@strataindia.com](mailto:info@strataindia.com) | **Website:** [www.strataindia.com](http://www.strataindia.com)